



Tradical® Hemcrete® Overview

Tradical® Hemcrete® is a unique, highly sustainable system for the creation of thermal walls, floors and roof insulation.

Tradical® Hemcrete® is a blend of specially prepared hemp shiv (Tradical® HF) and a special lime based binder (Tradical® HB). Together these products form a bio-composite building material.

Properties:

- › Carbon Capture
- › Low density
- › High thermal insulation
- › High sound insulation
- › High thermal inertia
- › Good vapour permeability
- › Good flexibility
- › Fire and pest resistance
- › Can significantly reduce CO2 emissions
- › Inherently airtight structures

Tradical® Hemcrete® a Lhoist Group developed product has been made available in the UK thanks to the collaboration of Lhoist UK and its partners Lime Technology, Castle Cement and Hemcore.

Tradical® Hemcrete® Products' Components

Tradical® HF is a hemp aggregate made from the stem of the hemp plant. It is chopped, graded and de-dusted to give a natural, sound and breathable product. Cultivated in the UK without agrochemicals, it is harvested annually. An easily renewable primary material, the industrial processing is mechanical and requires little energy and zero toxic products.



Tradical® HB is a special binder based on the purest hydrated air lime blended with selected hydraulic and pozzolanic materials. This ensures the perfect particle size distribution and setting characteristics to create the correct binder for use with hemp shives.

Tradical® Hemcrete® Performance

Studies have shown that up to 200kgs of CO₂ are emitted in the production of each square metre of walling for houses. For a typical house, this can mean up to 40 tonnes of CO₂ are emitted just in the construction of the walls.

Tradical® Hemcrete® products have the ability to make a very significant contribution in combating global climate change by effectively reducing CO₂ emissions. Fast growing hemp stores carbon during its growth and releases oxygen into the atmosphere. The overall combination of Tradical® Hemcrete® products is such that captured carbon is retained within the fabric of a Tradical® Hemcrete® building. This is typically 110kg/cubic metres of Tradical® Hemcrete®. Using Tradical® Hemcrete® you can reduce the CO₂ emissions for wall construction to zero or even less.

The sequestration of atmospheric CO₂ offers an existing opportunity to grow and produce sustainable, natural construction materials.

Only the use of Tradical® HF mixed with specific Tradical® HB or Tradical® special hemp binders guarantees quality results.